
Mechanical Pokers Dynapac/Pin Type

Model	TEK-MP1"	TEK-MP1.5"	TEK-MP2"	TEK-MP2.5"
Flexible Shaft (Dia. x Length)	25mm x 6mtr, 12mtr	40mm x 6mtr, 12mtr	50mm x 6mtr, 12mtr	60mm x 6mtr, 12mtr
Vibrating Head (Dia. x Length)	1 1/2" x 38mm	1 3/8" x 46.5mm	1 3/4" x 47.5mm	2" x 49mm
Vibration Frequency	13,000 – 14,000 vpm	12,000 – 13,000 vpm	11,500 – 12,500 vpm	11,000 – 12,000 vpm
Vibration Amplitude	0.8mm	1.60mm	2.00mm	2.40mm
Centrifugal Force	2,650 n	3,000 n	4,500 n	7,000 n



Flexible shaft mechanical poker vibrators for high vibration power in concrete and designed to meet the toughest site conditions. Available with a wide range of poker diameters from 25 to 68mm

- Single piece rotating pendulum vibrator, generating 12000 rpm.
 - Designed to the highest quality standard for long and trouble-free working life.
 - Over 6 meters of flexible shaft made of special spun steel and steel coil casing hose reinforcement.
-

-Choice of petrol or diesel power units with compact protective steel frame, easy to move on sites.

-Delivered with a universal Two-Dog drive coupling (compatible with Dynapac and Wacker), also Asian coupling kit available

-No special maintenance needed.